

## PRODUCT DATA SHEET AQ250 250MM DECORATIVE CLADDING



### GENERAL DESCRIPTION

A designer range of decorative internal wall cladding. A waterproof, hygienic, durable, virtually maintenance free cost-effective and practical alternative to tiling. Panels fit together with a tongue and groove joint to ensure quick and easy installation.

AQUA250 panels are constructed through PVC extrusion under a controlled environment overseen by Management and Quality Control systems. This is a hot PVC extrusion process. Due to the PVC composition, and the construction of the panels with additional strengthening cross members, the panels are rigid and strong; however, they are lighter, thinner and easier to handle than traditional PVC Wall panels, making them considerably easier to install.

For internal use only.

### MATERIAL

- : Recyclable Virgin PVC for consistence of quality
- : Calcium Carbonate (CaCO<sub>3</sub>)
- : Contains stabilisers, pigments and strengthening materials
- : Gloss UV resistant lacquer surface finish
- : None of these materials are classified as dangerous. No toxic affect. Non-hazardous.

### SIZE, WEIGHT AND HANDLING

- AQ250 Panels : 2700mm x 250mm x 5mm with 2 grooves; 4 grooves per pack; 2.7sqm per pack.  
: Minimum 2.2 kg/sqm; 6.4kg per pack & 33kg per outer carton of 5 packs including packaging.

### STORAGE AND HANDLING

- : Store flat and fully supported
- : No specific handling requirements
- : Outer cartons – beware of heavy weight. 2 persons are required to handle
- : Protect edges and decorative surface from damage during handling.

### TECHNICAL PROPERTIES

Fire Rating	Class 1 Fire Rating
Thermal Resistance	Remain stable up to 50°. Not for use behind or close to an oven, direct heat source, hob or other heat output.
Chemical Resistance	PVC is resistant to caustics, mineral, oil and fast foods
Impact Resistance	Test EN 13245-1:2004L Pass: 5 Joules at 23°

### WATER AND RAIN

Panels should not be left outside, and never be subject to rain (which may contain acids). If left outside, rain and water on panels can also magnify the effect of direct UV sunlight rays and discolour panels.

## UV RESISTANCE

Special UV resistant lacquers have been developed for the panels, however panels should not be left outside in direct sunlight.

## PREPARATIONS

AQUA250 Wall & Ceiling cladding panels are very easy to cut using a rough bladed saw, table saw or with a utility knife by scoring the décor surface. While cutting you must be aware that sharp edges may be encountered which should be smoothed off.

While preparing the panel boards, gloves and protective eye wear should always be worn.

When cutting the panels with a jigsaw or circular saw, cut with decorative face downwards.

When cutting the panels with a handsaw, cut with decorative face upwards.

## CLEANING

AQUA250 PVC Panels should only be cleaned with STORM Anti-bactericidal cleaner or any other non-abrasive cleaner (any cleaner/detergent which contains bleach MUST NOT be used).

Scouring products or powders should not be used.

Acetone, halogenated carbon hydrates, esters, ketone, ethers and alcohols should not be used.

## INSTALLATION

Panels should be fixed using a solvent free adhesive. It is recommended that 100% adhesive cover is achieved on the back of the board. Panels can be mechanically fixed (nail or staple) through the lip on the back of the groove.

## FREQUENTLY ASKED QUESTIONS

### What is AQ250 Decorative Cladding?

*AQ250 is a Decorative Cladding for use on walls and ceilings, with a range of PVC trims in 3 colours.*

### What is AQ250 Decorative Cladding used for?

*AQ250 Decorative Cladding is used where a decorative finish is required along with a water resistant feature mainly used in domestic washroom areas.*

### What is the best thing about AQ250 Decorative Cladding?

*The best thing about AQ250 Decorative Cladding is the large option of decorative finishes and range of trims available.*

### Why should end users use STORM's AQ250 Decorative Cladding instead of a competitors?

*You should consider using STORM's AQ250 Decorative Cladding because of its availability, extensive colour and design options backed with STORM's unique marketing support.*

### Who are the type of customers that commonly use AQ250 Decorative Cladding (which industries/sectors/job types)

*AQ250 is most commonly used by DIY enthusiasts, decorators and the home improvement sector.*

### Where is AQ250 Decorative Cladding most commonly installed?

*AQ250 Decorative Cladding would be most commonly installed in bathrooms, wetrooms etc.*

### When should AQ250 Decorative Cladding be considered and installed?

*AQ250 Decorative Cladding should be considered when refurbishment work is carried out within properties in a washroom area.*