

L10 specifications

350 PVC-U WINDOWS

PVC-U CASEMENT WINDOWS – EUROLOGIK

Manufacturer: Eurocell
Web: eurocell.co.uk
Email: info@eurocell.co.uk
Tel: 01773 842100
Fax: 01773 842109
Address: Fairbrook House, Clover Nook Road,
 Alfreton, Derbyshire DE55 4RF



Product reference: Eurologik 70mm window system

Size:	Min / max sizes	Width (mm)	Height (mm)
Top hung (espag)		Min: 320	Min: 375
		Max: 1200	Max: 1350
Side hung		Min: 400	Min: 320
		Max: 750	Max: 1500

Style: Eurologik Chamfered or Sculptured Ovolo

Colour / finish: White internally / White externally

Glazing: 28 mm double-glazed insulating unit, glazed internally
 4mm Float / 20mm Butyl Spacer / 4mm Saint Gobain Total +
 To achieve U-value of 1.4

Cill: 85mm stub cill / 150mm / 180mm / 225mm

Ironmongery / Accessories: As per fabricators specifications

Ventilation: As required to meet current regulations
 Approved Manufacturers: Glazpart, Titon, RW Simon, Greenwood, Brookvent

If you require more information, contact:



0800 988 3042



info@eurocell.co.uk