

L10 specifications

# 350 PVC-U WINDOWS

## PVC-U CASEMENT WINDOWS – MODUS

**Manufacturer:** Eurocell  
**Web:** eurocell.co.uk  
**Email:** info@eurocell.co.uk  
**Tel:** 01773 842100  
**Fax:** 01773 842109  
**Address:** Fairbrook House, Clover Nook Road, Alfreton, Derbyshire DE55 4RF



**Product reference:** Modus 75mm window system – standard sash casement

| Size:            | Min / max sizes                | Width (mm) | Height (mm) |
|------------------|--------------------------------|------------|-------------|
| Top hung (espag) | Min: 320                       | Min: 320   | Min: 375    |
|                  | Max: 1200                      | Max: 1200  | Max: 1350   |
| Side hung        | Min: 400                       | Min: 400   | Min: 320    |
|                  | Max: 750                       | Max: 750   | Max: 1500   |
| Fixed            | Max: 3000                      | Max: 3000  | Max: 2400   |
|                  | Combined width and height 5400 |            |             |

**Colour / finish:** White internally / White externally

**Glazing:** 28 mm double-glazed insulating unit, glazed internally (U Value 1.1 W/m<sup>2</sup>K)  
 44 mm triple-glazed insulating unit, glazed internally (U Value 0.7 W/m<sup>2</sup>K)

**Cill:** 85mm / 150 mm / 180mm

**Ironmongery / Accessories:** Hinges – Cotswold  
 Locking – A 6-point locking (four mushroom bolts and two shoot bolts) MACO MSPAG shootbolt and keeps (operated by a key locking ESPAG handle) (MODUS variant)  
 1 of pair of cavity closing wedges  
 2 of Maco hinge protectors (PAS 24:2012 requirement)  
 Screws - SFS

**Ventilation:** As required to meet current regulations  
 Approved Manufacturers: Glazpart, Titon, RW Simon, Greenwood, Brookvent

If you require more information, contact:



0800 988 3042



info@eurocell.co.uk