

L10 specifications

350 PVC-U WINDOWS

PVC-U TILT & TURN WINDOWS – MODUS

Manufacturer: Eurocell
Web: eurocell.co.uk
Email: info@eurocell.co.uk
Tel: 01773 842100
Fax: 01773 842109
Address: Fairbrook House, Clover Nook Road, Alfreton, Derbyshire DE55 4RF



Product reference: Modus 75mm tilt and turn window system

Size:	Min / max sizes	Width (mm)	Height (mm)
Tilt and turn windows		Min: 550 Max: 1500	Min: 550 Max: 1500

* Dependant on size and location

Colour / finish: White internally / White externally

Glazing: 28 mm double-glazed insulating unit, glazed internally (U Value 1.1 W/m²K)
 44 mm triple-glazed insulating unit, glazed internally (U Value 0.7 W/m²K)

Cill: 85mm / 15mm / 180mm

Ironmongery / Accessories: Hinges – MACO Concealed Security Gearing
 Locking – A 6-point locking (four mushroom bolts and two shoot bolts) MACO MSPAG shootbolt and keeps (operated by a key locking Tilt & Turn Handle) (MODUS variant)
 1 of pair of cavity closing wedges
 2 of Maco hinge protectors (PAS 24:2012 requirement)
 Screws – SFS

Ventilation: As required to meet current regulations
 Approved Manufacturers: Glazpart, Titon, RW Simon, Greenwood, Brookvent

If you require more information, contact:



0800 988 3042



info@eurocell.co.uk