

## Silversil Br. Lead

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Silversil Br. Lead  
 Registration number REACH : Not applicable (mixture)  
 Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Sealing compound

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

##### Manufacturer of the product

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):  
 +32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

#### 2.2. Label elements

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

##### Supplemental information

EUH208 Contains: 2-butanone oxime. May produce an allergic reaction.

#### 2.3. Other hazards

No other hazards known

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
2-butanone oxime	96-29-7 202-496-6	0.1%<C<1%	Carc. 2; H351 Skin Sens. 1; H317 Acute Tox. 4; H312 Eye Dam. 1; H318	(1)(2)	Reaction product

# Silversil Br. Lead

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,  
<0.03% aromatics  
01-2119827000-58

20%<C<40% Asp. Tox. 1; H304

(1)(10)

UVCB

- (1) For H-statements in full: see heading 16  
(2) Substance with a Community workplace exposure limit  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, seek medical advice.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

#### After ingestion:

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

No effects known.

##### After skin contact:

No effects known.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2  
Major fire: Class B foam (not alcohol-resistant).

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.  
Major fire: Water; risk of puddle expansion.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours and formation of metallic fumes.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

No specific fire-fighting instructions required.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

##### Suitable protective clothing

See heading 8.2

### 6.2. Environmental precautions

Contain released product. Use appropriate containment to avoid environmental contamination.

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

2 / 12

# Silversil Br. Lead

## 6.3. Methods and material for containment and cleaning up

Scoop solid spill into closing containers. Clean contaminated surfaces with a soap solution. Wash clothing and equipment after handling.

## 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Store in a dry area. Store at room temperature. Meet the legal requirements. Max. storage time: 1 year(s).

#### 7.2.2 Keep away from:

Heat sources.

#### 7.2.3 Suitable packaging material:

Synthetic material.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m <sup>3</sup>
	Short time value	10 mg/m <sup>3</sup>

##### The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m <sup>3</sup>
---------------------------	---	---------------------

##### Germany

Butanonoxim	Time-weighted average exposure limit 8 h (TRGS 900)	0.3 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1 mg/m <sup>3</sup>

##### USA (TLV-ACGIH)

Mineral oil, pure, highly and severely refined (I): Inhalable fraction	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m <sup>3</sup> (I)
---	--	-------------------------

##### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Oil Mist (Mineral)	NIOSH	5026

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 DNEL/PNEC values

##### DNEL/DMEL - Workers

##### 2-butanone oxime

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	9 mg/m <sup>3</sup>	
	Long-term local effects inhalation	3.33 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1.3 mg/kg bw/day	
	Acute systemic effects dermal	2.5 mg/kg bw/day	

##### DNEL/DMEL - General population

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

3 / 12

# Silversil Br. Lead

## 2-butanone oxime

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.7 mg/m <sup>3</sup>	
	Long-term local effects inhalation	2 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.78 mg/kg bw/day	
	Acute systemic effects dermal	1.5 mg/kg bw/day	

## PNEC

### 2-butanone oxime

Compartment	Value	Remark
Fresh water	0.256 mg/l	
Aqua (intermittent releases)	0.118 mg/l	
STP	177 mg/l	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Keep container tightly closed. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Insufficient ventilation: wear respiratory protection.

#### b) Hand protection:

Gloves.

- materials (good resistance)

Nitrile rubber.

#### c) Eye protection:

Safety glasses.

#### d) Skin protection:

Protective clothing.

### 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Paste
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Not easily combustible
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	> 120 °C
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	No data available
Solubility	Water ; insoluble
Relative density	0.97
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

### 9.2. Other information

Surface tension	No data available
Extrapolated kinematic viscosity	> 30 seconds ; 4 mm
Absolute density	970 kg/m <sup>3</sup>

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

4 / 12

# Silversil Br. Lead

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Keep away from naked flames/heat.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: formation of CO, CO<sub>2</sub> and small quantities of nitrous vapours and formation of metallic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### 11.1.1 Test results

#### Acute toxicity

##### Silversil Br. Lead

No (test)data on the mixture available

Judgement is based on the relevant ingredients

##### 2-butanone oxime

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2326 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 1000 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 4.83 mg/l air	4 h	Rat (male/female)	Experimental value	

##### hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5266 mg/m <sup>3</sup> air	4 h	Rat (male/female)	Experimental value	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### Silversil Br. Lead

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
	Not irritating	OECD 437				Experimental value	
	Not irritating					Expert judgement	

Judgement is based on the relevant ingredients

##### 2-butanone oxime

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Slightly irritating	Other	24 h	1; 24; 48; 72 hours	Rabbit	Experimental value	

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

5 / 12

# Silversil Br. Lead

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## Conclusion

Not classified as irritating to the skin  
 Not classified as irritating to the eyes  
 Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### Silversil Br. Lead

No (test) data on the mixture available  
 Judgement is based on the relevant ingredients

### 2-butanone oxime

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing	Equivalent to OECD 406	24 h	24; 48 hours	Guinea pig (female)	Experimental value	

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (female)	Read-across	

## Conclusion

Not classified as sensitizing for inhalation  
 Not classified as sensitizing for skin

## Specific target organ toxicity

### Silversil Br. Lead

No (test) data on the mixture available  
 Judgement is based on the relevant ingredients

### 2-butanone oxime

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	LOAEL	US EPA	40 mg/kg bw/day	General	Clinical signs; mortality; body weight; food consumption	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	< 40 mg/kg bw/day	Blood	Change in the haemogramme/ blood composition	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOEL	US EPA	125 mg/kg bw/day	Central nervous system	Behavioural disturbances	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	312 ppm	Blood	Change in the haemogramme/ blood composition	13 week(s)	Rat (female)	Experimental value
Oral	NOAEL	US EPA	625 ppm	Blood	Change in the haemogramme/ blood composition	13 week(s)	Rat (male)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 412	90 mg/m <sup>3</sup> air	Blood	Change in the haemogramme/ blood composition	4 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

6 / 12

# Silversil Br. Lead

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	> 5000 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male/female)	Read-across
Dermal	NOAEL	Equivalent to OECD 411	> 495 mg/kg/d		No effect	13 weeks (daily, 5 days/week)	Rat (male/female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10186 mg/m <sup>3</sup> air		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

Silversil Br. Lead

No (test) data on the mixture available

2-butanone oxime

Result	Method	Test substrate	Effect	Value determination
Ambiguous	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value
Negative	Equivalent to OECD 482	Rat liver cells		Experimental value

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Read-across
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Read-across

## Mutagenicity (in vivo)

Silversil Br. Lead

No (test) data on the mixture available

Judgement is based on the relevant ingredients

2-butanone oxime

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Other	3 day(s)	Drosophila melanogaster (male)	Male reproductive organ	Experimental value
Negative	Other		Rat (male/female)		Experimental value

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 483	8 weeks (6h/day, 5 days/week)	Mouse (male)	Male reproductive organ	Read-across
Negative	Equivalent to OECD 475		Rat (male/female)	Bone marrow	Read-across
Negative	Equivalent to OECD 474	24 h - 72 h	Mouse (male/female)	Bone marrow	Read-across

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

Silversil Br. Lead

No (test) data on the mixture available

Judgement is based on the relevant ingredients

2-butanone oxime

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	EPA OTS 798.3300	0.27 mg/l	≥ 1 year(s) (6h/day, 5 days/week)	Rat	No carcinogenic effect		Experimental value
Inhalation (vapours)	Dose level	EPA OTS 798.3300	374 ppm	≥ 1 year(s) (6h/day, 5 days/week)	Rat	Carcinogenicity	Liver	Experimental value

## Conclusion

Not classified for carcinogenicity

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

7 / 12



# Silversil Br. Lead

## Reproductive toxicity

### Silversil Br. Lead

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### 2-butanone oxime

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL (F1)	OECD 414	600 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
	LOAEL (P)	OECD 414	60 mg/kg bw/day	10 day(s)	Rat	Spleen enlargement/affection	Spleen	Experimental value
Effects on fertility	NOAEL	US EPA	≥ 200 mg/kg/d		Rat (male/female)			Experimental value

#### hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	OECD 414	> 1000 mg/kg bw/day	10 day(s)	Rat (female)	No effect		Experimental value
Maternal toxicity	NOAEL	OECD 414	> 1000 mg/kg bw/day	10 day(s)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL (P)	Equivalent to OECD 422	> 1000 mg/kg bw/day		Rat (male/female)	No effect		Read-across
	NOAEL (P)	Equivalent to OECD 421	> 1000 mg/kg bw/day		Rat (male/female)	No effect		Read-across

### Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### Silversil Br. Lead

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

### Silversil Br. Lead

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Silversil Br. Lead

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

#### 2-butanone oxime

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oryzias latipes	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	201 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	11.8 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	2.56 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	OECD 204	≥ 100 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

8 / 12



# Silversil Br. Lead

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	Equivalent to OECD 203	> 1028 mg/l	96 h	Scophthalmus maximus	Semi-static system	Salt water	Experimental value; GLP
Acute toxicity crustacea	LL50	ISO 14669	> 3193 mg/l	48 h	Acartia tonsa	Static system	Salt water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	ISO 10253	> 10000 mg/l	72 h	Skeletonema costatum	Static system	Salt water	Experimental value; GLP
Long-term toxicity fish	NOELR		> 1000 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Growth rate
Long-term toxicity aquatic crustacea	NOELR		> 1000 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR
Toxicity aquatic micro-organisms	EC50	OECD 209	> 100 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

## Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

### Biodegradation water

Method	Value	Duration	Value determination
OECD 306: Biodegradability in Seawater	74 %; GLP	28 day(s)	Experimental value

## Conclusion

Contains readily biodegradable component(s)

## 12.3. Bioaccumulative potential

Silversil Br. Lead

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

2-butanone oxime

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	0.5 - 5.8; GLP	42 day(s)	Cyprinus carpio	Experimental value

### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.63		Experimental value

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

## Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

## 12.4. Mobility in soil

2-butanone oxime

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.55	QSAR

hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	0.3 %		92.8 %	6.8 %	0.1 %	Calculated value

## Conclusion

Contains component(s) that adsorb(s) into the soil  
Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Other adverse effects

Silversil Br. Lead

### Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

9 / 12

# Silversil Br. Lead

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

## Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### 2-butanone oxime

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

## SECTION 14: Transport information

### Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

#### 14.1. UN number

Transport	Not subject
-----------	-------------

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	
Classification code	

#### 14.4. Packing group

Packing group	
Labels	

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	
Limited quantities	

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
1.08 %	
10.48 g/l	

#### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
2-butanone oxime hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

10 / 12

# Silversil Br. Lead

	<p>1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;          (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;          (c) hazard class 4.1;          (d) hazard class 5.1.</p>	<p>fiscal reasons, or perfume, or both, if they:          — can be used as fuel in decorative oil lamps for supply to the general public, and,          — present an aspiration hazard and are labelled with R65 or H304,          4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).          5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:          a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";          b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";          c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.          6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.          7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
--	--	---

## National legislation Belgium

Silversil Br. Lead  
 No data available

## National legislation The Netherlands

Silversil Br. Lead  
 No data available

## National legislation France

Silversil Br. Lead  
 No data available

## National legislation Germany

Silversil Br. Lead

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4) and Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) of 18 April 2017
-----	---

## 2-butanone oxime

TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	Butanonoxim; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Sensibilisierende Stoffe	Butanonoxim; Sh; Hautsensibilisierende Stoffe
Hautresorptive Stoffe	Butanonoxim; H; Hautresorptiv

## hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

TA-Luft	5.2.5
---------	-------

## National legislation United Kingdom

Silversil Br. Lead  
 No data available

## Other relevant data

Silversil Br. Lead  
 No data available

## hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

TLV - Carcinogen	Mineral oil, pure, highly and severely refined; A4
------------------	--

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H-statements referred to under heading 3:

- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H351 Suspected of causing cancer.

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

11 / 12

# Silversil Br. Lead

(*)	INTERNAL CLASSIFICATION BY BIG
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 8.2

Publication date: 2008-06-04

Date of revision: 2017-11-06

Revision number: 0303

Product number: 46302

12 / 12