

SAVE
UP TO
A DAY
ON INSTALLATION

NEW slateskin®

The GRP sheet roof tile system that gives
a traditional slate-effect in half the time

eurocell®
All together better



slateskin[®]

THE **NEW!** SHEET TILED ROOF SYSTEM
DESIGNED TO SAVE YOU TIME ON-SITE



Great looking, long lasting slate effect roofs – in half the time!

At Eurocell, we're always exploring new ways to help our trade customers deliver a better job. Our latest is SlateSkin – a sheet tiling system that allows you to fit a realistic slate-effect, water-resistant system to Equinox conservatory roofs in around 50% less time.

There's never been a better way to finish the job beautifully and provide your customers with an attractive, hard-wearing roof that will stay looking good for 25-years and beyond.

When it comes to helping you add a beautiful and durable finishing touch to your building projects, it's taking convenience to new heights.

Get the job finished faster

SlateSkin is specially designed to help you stay ahead of schedule when you're up on the roof. With multiple tile courses built in to each sheet, the system reduces the time and hassle spent positioning and nailing tiles with no compromise on build quality or aesthetics. It also helps you make light work of roofing with loads less carrying and handling required.

So it doesn't just look good for your customer. It's also an extremely attractive prospect for busy installers.

SlateSkin is available as part of an Equinox tiled roof solution.


WHY CHOOSE SLATESKIN?



Up to 50% faster to install than authentic conservatory tiling methods



Saves you time and money!



Easy-fit sheet system



Only tile system tested to achieve 5° pitch



Attractive slate-effect finish



Tough and hard-wearing



Precision-engineered for enhanced performance



25-year guarantee for peace of mind

Hassle-free installation

Give us your dimensions when you order your Equinox roof and we'll do the rest. Using state-of-the-art equipment and the same precision measurements used in the manufacture of our market leading PVC-U systems, our engineers will create all the components you need including the tile sheets, hip end caps and ridge and hip top caps.

We'll even pre-cut and colour code for fast identification on-site. All you need to do is quickly and easily assemble the pieces in-situ to create a beautiful, slate effect roof that's fully water resistant, superbly strong and highly durable.

No condensation

Because there are fewer gaps than separate tiles, SlateSkin is water resistant and prevents moisture getting into the roof space. Whilst precision cutting ensures that each component fits together seamlessly to further increase the roof's weatherproofing qualities.

No compromise on build quality

SlateSkin gives you the reassurance of the right fit first time, every time. Plus, you can call on the benefits of SlateSkin for projects of various sizes, making it as versatile and flexible as composite slate and even clay or concrete roof tiles.

If the conservatory roof is a non-standard Edwardian or 3 bay Victorian, then the 3 or 5 way top cap will need modifying and hip caps may need to be scribed together to create a water tight crown point. This can be complex and time consuming.

AA fire-performance for peace of mind

SlateSkin, when fitted to an Equinox tiled roof, comes with the added reassurance of excellent fire resistance meaning you can install it in virtually any location. The combined system achieved a rating of EXT.S.AA when tested to BS476 Part 3:2004, External Fire Exposure Roof Test*.

*No flame spread occurred therefore the product will be classified as 'A'.
No flaming penetration occurred therefore the product will be classified as 'A'.
The resulting classification obtained from the tests above is EXT.S.AA.

AUTHENTIC SLATE LOOKS

slateskin®

AN ATTRACTIVE, MODULAR SYSTEM

Realistic slate-effect finish

SlateSkin uses the same attractive finish as composite slate tiles. To the untrained eye, it's difficult to tell the difference between this slate-effect product and traditional slate, helping your new roof complement even the most traditional property.

Colour-matched screws

Your system will be supplied with all necessary screws with colour-matched heads for a co-ordinated finish in less time.

Long-lasting performance

SlateSkin comes with a 25-year guarantee so you can be sure that once installed, it won't let you or your customers down.

Widest range of pitches

Lightweight construction allows you to set the roof pitch anywhere from just 5°* to 35°. SlateSkin is the only tile system tested to achieve 5° pitch and perfect for lean-to projects, giving you the edge over installers who use conventional roofing when you're quoting on lean-to designs.

* 5° pitch available using SlateSkin only. 10° pitch available using alternative tiles.

** Maximum SlateSkin single facet size is 6 metres.



Tile sheet **

ERS 1340

Available in: 6m (ERS 1340GY2-6M)

4m (ERS 1340GY2-4M)

2m (ERS 1340GY2-2M)



Ridge length cap (6m)
ERS 1321GY2-FG



90° Victorian hip end cap
ERS 1329GY2-FG



135° Edwardian hip end cap
ERS 1325GY2-FG



5-way ridge top cap
ERS 1326GY2 (25)
Also available in: 15° (ERS 1330GY2)
20° (ERS 1331GY2)
30° (ERS 1332GY2)
35° (ERS 1333GY2)



3-way ridge top cap
ERS 1322GY2 (25)
Also available in: 15° (ERS 1334GY2)
20° (ERS 1335GY2)
30° (ERS 1336GY2)
35° (ERS 1337GY2)

GRP Ridge Gable End Cap
ERS 1338GY2-FG





CUT INSTALLATION TIMES IN HALF

Choosing to finish your roof installations with SlateSkin can save you up to half a day in labour time. Here's how:



1

LAY THE PRE-CUT SHEET TILE COMPONENTS

**This step:
35 minutes**

Total run time: 35 minutes



2

PREPARE RIDGE FRAMEWORK

**This step:
5 minutes**

Total run time: 40 minutes

The time savings were calculated using a 3.8m x 2.9m Victorian conservatory roof, and it is assumed that the roof framework is correctly prepared and installed. This includes insulation, boarding and weatherproofing, which are required before the SlateSkin product can be installed. Time savings will vary by the roof size and complexity. Pictures for illustration purposes only.



COMPONENTS SUPPLIED PRE-CUT TO SIZE



BE SAFE WHEN WORKING AT HEIGHT

Practices when working at height must conform to the latest Work at Height Regulations.

For more details, visit: www.legislation.gov.uk www.hse.gov.uk/work-at-height www.hse.gov.uk/toolbox/height.htm



AFFIX RIDGE CAPPING COMPONENTS

**This step:
40 minutes**

Total run time: 80 minutes



FIT THE RIDGE MOULDING TO COMPLETE

**This step:
5 minutes**

Total run time: 85 minutes



TOTAL TIME: 1hr 25m



Certificate No: EW6o6



(LABC achieved when installed with an Equinox® tiled roof system)



All together better

For more information about the new **slateskin**® slate-effect roofing system from Eurocell, call our customer services team on **0800 988 3047**, or visit eurocell.co.uk/slateskin

Eurocell plc, Fairbrook House, Clover Nook Road, Alfreton, Derbyshire DE55 4RF



eurocell.co.uk